

IN THE CLAIMS

1. (Previously Presented) A sputtering target, comprising:
a target surface component comprising a target material;
a core backing component having a coupling surface and a back surface, wherein
the coupling surface is coupled to the target surface component; and
at least one surface area feature coupled to or located in the back surface of the
core backing component, wherein the surface area feature increases the
effective surface area of the core backing component, and wherein the core backing
component comprises a center cooling design.
2. (Original) The sputtering target of claim 1, wherein the target material comprises a
metal, a metal alloy or a combination thereof.
3. (Original) The sputtering target of claim 2, wherein the metal or metal alloy
comprises a transition metal.
4. (Previously Presented) The sputtering target of claim 2, wherein the metal or metal
alloy comprises copper, aluminum or titanium.
5. (Original) The sputtering target of claim 1, wherein the at least one surface area
feature comprises at least one concave feature, at least one convex feature or a
combination thereof.
6. (Original) The sputtering target of claim 5, wherein the at least one concave feature
comprises at least one concentric indentation.
7. (Original) The sputtering target of claim 5, wherein the at least one concave feature
comprises a dimple.
8. (Original) The sputtering target of claim 5, wherein the at least one concave feature

comprises a plurality of linear channels.

9. (Original) The sputtering target of claim 5, wherein the at least one convex feature comprises a plurality of linear ridges or protrusions.
10. (Original) The sputtering target of claim 5, wherein the at least one convex feature comprises a bump.
11. (Original) The sputtering target of claim 5, wherein the at least one convex feature comprises at least one concentric ridge or protrusion.
12. (Previously Presented) A sputtering target, comprising:
 - a target surface component comprising a target material;
 - a core backing component having a coupling surface and a back surface, wherein the coupling surface is coupled to the target surface component; and
 - at least one surface area feature coupled to or located in the back surface of the core backing component, wherein the surface area feature comprises a subtractive feature, an additive feature or a combination thereof, wherein the surface area feature increases the effective surface area of the core backing component, and wherein the core backing component comprises a center cooling design.
13. (Original) The sputtering target of claim 12, wherein the target material comprises a metal, a metal alloy or a combination thereof.
14. (Original) The sputtering target of claim 13, wherein the metal or metal alloy comprises a transition metal.
15. (Previously Presented) The sputtering target of claim 12, wherein metal or metal alloy comprises copper, aluminum or titanium.
16. (Original) The sputtering target of claim 12, wherein the at least one subtractive feature comprises at least one concentric indentation.

17. (Original) The sputtering target of claim 12, wherein the at least one subtractive feature comprises a dimple.
18. (Original) The sputtering target of claim 12, wherein the at least one subtractive feature comprises a plurality of linear channels.
19. (Original) The sputtering target of claim 12, wherein the at least one additive feature comprises a plurality of linear ridges or protrusions.
20. (Original) The sputtering target of claim 12, wherein the at least one additive feature comprises a bump.
21. (Original) The sputtering target of claim 12, wherein the at least one additive feature comprises at least one concentric ridge or protrusion.
22. (Previously Presented) A method of forming a sputtering target, comprising:
 - providing a target surface component comprising a surface material;
 - providing a core backing component comprising a backing material and having a coupling surface and a back surface;
 - providing at least one surface area feature coupled to or located in the back surface of the core backing component, wherein the surface area feature increases the effective surface area of the core backing component, and wherein the core backing component comprises a center cooling design allowing the cooling fluid to contact the center of the core backing component initially; and
 - coupling the surface target component to the coupling surface of the core backing component.
23. (Previously Presented) A method of forming a sputtering target, comprising:
 - providing a target surface component comprising a surface material;

providing a core backing component comprising a backing material and having a coupling surface and a back surface;

providing at least one surface area feature coupled to or located in the coupling surface of the core backing component, wherein the surface area feature increases the effective surface area of the core backing component, and wherein the core backing component comprises a center cooling design allowing the cooling fluid to contact the center of the core backing component initially; and

coupling the surface target component to the coupling surface of the core backing component.

24. (Previously Presented) A sputtering target, comprising:
 - an integrated target surface component and core backing component, wherein the surface component and the backing component comprise the same target material; and
 - at least one surface area feature that is on or integrated into the core backing component, wherein the surface area feature increases the effective component of the core backing component, and wherein the core backing component comprises a center cooling design allowing the cooling fluid to contact the center of the core backing component initially.
25. (Original) The sputtering target of claim 24, wherein the target material comprises a metal, a metal alloy or a combination thereof.
26. (Original) The sputtering target of claim 25, wherein the metal or metal alloy comprises a transition metal.
27. (Previously Presented) The sputtering target of claim 25, wherein the metal or metal alloy comprises copper, aluminum or titanium
28. (Original) The sputtering target of claim 24, wherein the at least one surface area

feature comprises at least one concave feature, at least one convex feature or a combination thereof.

29. (Original) The sputtering target of claim 28, wherein the at least one concave feature comprises at least one concentric indentation.
30. (Original) The sputtering target of claim 28, wherein the at least one concave feature comprises a dimple.
31. (Original) The sputtering target of claim 28, wherein the at least one concave feature comprises a plurality of linear channels.
32. (Original) The sputtering target of claim 28, wherein the at least one convex feature comprises a plurality of linear ridges or protrusions.
33. (Original) The sputtering target of claim 28, wherein the at least one convex feature comprises a bump.
34. (Original) The sputtering target of claim 28, wherein the at least one convex feature comprises at least one concentric ridge or protrusion.
35. (Previously Presented) A sputtering target, comprising:

an integrated target surface component and core backing component, wherein the sputtering target comprises a target material gradient; and

at least one surface area feature that is located on or integrated into the core backing component, wherein the surface area feature increases the effective component of the core backing component, and wherein the core backing component comprises a center cooling design.
36. (Original) The sputtering target of claim 35, wherein the target material comprises a metal, a metal alloy or a combination thereof.
37. (Original) The sputtering target of claim 36, wherein the metal or metal alloy comprises a transition metal.

38. (Previously Presented) The sputtering target of claim 36, wherein the metal or metal alloy comprises copper, aluminum or titanium.
39. (Original) The sputtering target of claim 35, wherein the at least one surface area feature comprises at least one concave feature, at least one convex feature or a combination thereof.
40. (Original) The sputtering target of claim 39, wherein the at least one concave feature comprises at least one concentric indentation.
41. (Original) The sputtering target of claim 39, wherein the at least one concave feature comprises a dimple.
42. (Original) The sputtering target of claim 39, wherein the at least one concave feature comprises a plurality of linear channels.
43. (Original) The sputtering target of claim 39, wherein the at least one convex feature comprises a plurality of linear ridges or protrusions.
44. (Original) The sputtering target of claim 39, wherein the at least one convex feature comprises a bump.
45. (Original) The sputtering target of claim 39, wherein the at least one convex feature comprises at least one concentric ridge or protrusion.